




One-gang device box. Cover has twistout for 2400 Series Raceway on each side, and one twistout for 500 and 700 Series Raceway on the top and bottom. Base has knockout to enable extension from existing single-gang, flush wall box and 1/2" trade size KOs. Accepts industry standard faceplates for electrical and communication devices. NOTE: Accepts NEMA single-gang standard faceplates. Certified to Canadian Safety Standards for sale in Canada. When ordering this product for Canada, add "C" to the beginning of the part number to denote Canadian versions, i.e. "CV2444" or "C2444-FW".

Features & Benefits

One-gang device box. Cover has twistout for 2400 Series Raceway on each side, and one twistout for 500 and 700 Series Raceway on the top and bottom.

Base has knockout to enable extension from existing single-gang, flush wall box and 1/2" trade size KOs.

Accepts industry standard faceplates for electrical and communication devices. NOTE: Accepts NEMA single-gang standard faceplates.

Certified to Canadian Safety Standards for sale in Canada. When ordering this product for Canada, add "C" to the beginning of the part number to denote Canadian versions, i.e. "CV2444" or "C2444-FW".

Specifications

General Info

Product Line	Wiremold	Replaced by Part Number	C2448-FW
Color	Fog White	UPC Number	786776132489
Country Of Origin	United States	Material	Steel
Product Series	2400 Series	Installation Location	On Wall
Application Sector	Commercial	Standard	cULus Listed Raceway: FileE4376 Guide RJBT. Fittings: File E41751 Guide RJPR. Base & Blank Cover: Meets Article 386 of NEC. Meets Section 12-600 of CEC.
Warranty Type	1-Year from Installation or 2-Years from Day of Sale	Type	Raceway Device Box

Dimensions

Product Width US	4.625 in	Product Weight US	0.548 lb
Product Height US	1.75 in	Product Length US	2.875 in
Knockout Size	1/2 in		

Additional Information

RoHS Compliant	Yes	Product Environmental Profile	Yes
----------------	-----	-------------------------------	-----

Technical Information

Is Pre-Wired	No	Number of Gangs	1
Indoor/Outdoor	Indoor	Voltage	600.0 V