Certificate of Compliance

Certificate Number:

UL-US-L42190-19-52904102-3

Report Reference:

E42190-20250228

Issue Date:

2025-06-17

Issued to:

PASS & SEYMOUR INC
50 Boyd Ave Syracuse, NY 13209
United States

This certificate confirms that representative samples of:
KCXS - Ground-fault Circuit Interrupters

See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

UL 943, 5th Ed., Issue Date: 2016-05-17, Revision Date: 2018-02-23

Additional Information:
See UL Product iQ® at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

David Piecuch
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2024 UL LLC. All rights reserved.
Form-ULID-019496 – ver 1.0

CERTIFICATE OF COMPLIANCE

Certificate number	UL-US-L42190-19-52904102-3
Report reference	E42190-20250228
Date	2025-06-17

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model(s): 1597, 1597TRSGL, 2097TRSGL

Model(s): P Series BASE CAT. NO. SUFFIXES (no specific order) 1597 XXX Y M or A ZZ 2097 XXX Y M or A ZZ Prefix = 0 to 4 characters for commercial purposes only 1597 = 15 Amp 120 V 2097 = 20 Amp 120 V XX = 0 to 223 letters denoting plugs and connectors the device use. Typical Examples: “CM” = Denotes a device with a right angle plug for input and an output cord to which the user can install a connector manual (field wirable). “CS” = Denotes a device with a right angle plug for input and an output cord with straight connector. “PC” = Denotes a device with straight plug and connector. “TC” = Denotes a device with straight plug and Tricord connector. “TL” = Denotes a device with Turn Lock plug and connector. “FF” = Denotes an inline device with no factory attached input or output cords. “FTC” = Denotes an inline device with no factory attached input cord and a Tricord connector output. Y = 0 or 1 Letter or Number denoting the total cord length. Typical Examples: “6’” = Denotes a device with total approx. 6’ cord. “2’” = Denotes a device with total approx. 2’ cord. “1’” = Denotes a device with total approx. 1’ cord. “A” = Denotes a device auto reset when power on “M” = Denotes a device manual reset when power on ZZ = 0 to 2 alphanumeric characters denoting the device housing color.

Ground Fault Circuit Interrupters, Model(s): PL200L, PS150S, PS200S

Receptacle type, Model(s): 1597NTLTR, 2097NTLTR

Receptacle type self tests, Model(s): Type A, Type E, Type F, Type M

Receptacle type tamper resistant, general grade, self tests, Model(s): Type B

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

© 2024 UL LLC. All rights reserved.